

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
21 October 2004 (21.10.2004)

PCT

(10) International Publication Number
WO 2004/091254 A2

(51) International Patent Classification⁷:

H04R 3/00

(21) International Application Number:

PCT/IB2004/001025

(22) International Filing Date: 26 March 2004 (26.03.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

03100947.5 8 April 2003 (08.04.2003) EP

(71) Applicant (for DE only): **PHILIPS INTELLECTUAL PROPERTY & STANDARDS GMBH [DE/DE]**; Stein-damm 94, 20099 Hamburg (DE).

(71) Applicant (for all designated States except DE, US): **KONINKLIJKE PHILIPS ELECTRONICS N. V. [NL/NL]**; Groenewoudseweg 1, 5621 BA Eindhoven (NL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **LIEB, Markus [DE/DE]**; c/o Philips Intellectual Property & Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE).


(74) Agent: **VOLMER, Georg**; Philips Intellectual Property & Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR REDUCING AN INTERFERENCE NOISE SIGNAL FRACTION IN A MICROPHONE SIGNAL



WO 2004/091254 A2

(57) Abstract: The invention discloses a method of reducing an interference noise signal fraction in a microphone signal, which method is based on estimating the interference noise signal fraction from a virtually pure interference noise signal and does not require any additional microphones. It is an essential feature of the method according to the invention that the signal which is used as a basis for estimating the interference noise signal fraction in the microphone signal of interest is received by means of one or more inversely operated loudspeakers. There is no need to install further microphones, particularly in situations where there are already one or more loudspeakers as components of an audio system. Such a situation arises for example in any motor vehicle fitted with an audio system.



GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*